

# JCM 200 U

Magnetic base drill unit up to 2" (50 mm)

Part Number: 7 27 04 461 12 0



The lightweight JCM 200 U 2-speed tool with MT 3 holder offers a universal range of applications and high flexibility for all applications.

- Compact with high functionality for universal use on construction site and in the workshop.
- Simple top mounted controls avoid mix-ups and can be clearly seen by the operator.
- Double drill motor guide for use with very large drilling tools.
- Forward and reverse rotation.
- Electronic speed setting.
- Slugger high-power motor with stable speed.
- High magnetic holding force.
- Convenient magnetic holding force indicator.
- Integrated coolant tank.
- Feed handwheel can be removed from one side to the other.
- MT 3 interface.
- Optional Weldon QuickIN arbor is available. (uses standard 3/4" Weldon shank cutters).



# JCM 200 U

Magnetic base drill unit up to 2" (50 mm)

Part Number: 7 27 04 461 12 0

## Technical data

---

Carbide cutter max. dia. in (mm)	2 (50)
HSS cutter max. dia. in (mm)	1 9/16 (40)
Cutter max. drilling depth [optional] in (mm)	2 [3] (50 [75])
Twist drill max. dia. in (mm)	7/8 (23)
Tapping max. in (M)	1/2 (16)
Countersinking max. dia. in (mm)	2 (50)
Reaming max. dia. in (mm)	7/8 (23)
Power consumption W	1 200
Power output W	610
1st speed rpm	130 – 260
2nd speed rpm	260 – 520
Cutter holder	QuickIN
Tool mounting MT	3
Stroke / stroke range in	5 11/16 / 12 3/8
Magnetic holding force lbs (N)	2 750 (12 500)
Magnetic foot dimensions in	7 11/16 x 3 9/16
Cable with plug ft (m)	13 (4)
Weight according to EPTA lbs (kg)	30.6 (13.9)

## Price includes:

---

1 case
1 coolant tank
1 safety strap
1 chip hook
1 pilot pin 4 1/8" (105 mm)
1 contact guard
1 drift key