



W9-115 Kit
4 1/2" Angle Grinder

NEW



W9-115
4 1/2" Angle Grinder

NEW

Model	W9-115 Kit 600354850	W9-115 600354420
Maximum wheel diameter	4-1/2"	4-1/2"
Amps	8.5	8.5
Rated input watts	900	900
No-load speed (RPM)	10,500	10,500
Maximum torque (inch lbs.)	22.1 inch lbs.	22.1 inch lbs.
Switch Type	Lock-on slide	Lock-on slide
LongLife motor	•	•
AC/DC capability	•	•
Metabo safety slip clutch	•	•
Low profile aluminum die-cast gear housing	•	•
Rotatable gear housing	•	•
Burst-proof guard w/ 7 stops	•	•
Auto-stop carbon brushes	•	•
Winding protection grid	•	•
Arbor size	7/8"	7/8"
Spindle thread	5/8"-11	5/8"-11
Tool weight	4.6 lbs.	4.6 lbs.
Shipping weight	8.9 lbs.	5.94 lbs.
Length	11.9"	11.9"
Carrying case	344454180 (standard)	344454180 (optional)
Standard equipment:		
Type 27 wheel guard	339204490	339204490
Side handle	314000540	316046590
Inner flange	341031290	341031290
Locking nut	341101480	341101480
Spanner wrench	623934000	623934000
Diamond wheel	624306000	
Optional equipment:		
Quick-Clip on Type 1 cutting guard	630351000	630351000



W9-115 Quick
4 1/2" Angle Grinder

NEW



WP9-115 Quick
4 1/2" Angle Grinder
with non-locking paddle switch

NEW



WP12-115 Quick
4 1/2" Angle Grinder
with non-locking paddle switch

NEW

Model	W9-115 Quick 600371420	WP9-115 Quick 600380420	WP12-115 Quick 600410420
Maximum wheel diameter	4-1/2"	4-1/2"	4-1/2"
Amps	8.5	8.5	10.5
Rated input watts	900	900	1250
No-load speed (RPM)	10,500	10,500	11,000
Maximum torque (inch lbs.)	22.1 inch lbs.	22.1 inch lbs.	30.1 inch lbs.
Switch Type	Lock-on slide	Non-locking paddle	Non-locking paddle
LongLife motor	•	•	•
AC/DC capability	•	•	•
Metabo safety slip clutch	•	•	•
Quick wheel change system	•	•	•
Low profile aluminum die-cast gear housing	•	•	•
Rotatable gear housing	•	•	•
Burst-proof guard w/ 7 stops	•	•	•
Vibration dampened side handle	•	•	
Anti-vibration side handle			•
Auto-stop carbon brushes	•	•	•
Winding protection grid	•	•	•
Arbor size	7/8"	7/8"	7/8"
Spindle thread	5/8"-11	5/8"-11	5/8"-11
Tool weight	4.6 lbs.	4.6 lbs.	5.3 lbs.
Shipping weight	5.94 lbs.	6 lbs.	6.54 lbs.
Length	11.4"	11.4"	12.4"
Carrying case (optional)	344454180	344454180	344454180
Standard equipment:			
Type 27 wheel guard	339204490	339204490	339204490
Side handle	316046590	316046590	314000970
Inner flange	341031290	341031290	341031290
Locking nut	316055450	316055450	316055450
Optional equipment:			
Quick-Clip on Type 1 cutting guard	630351000	630351000	630351000
Dust filter			630792000



W9-125
4 1/2" / 5" Angle Grinder

NEW



WP9-125 Quick
4 1/2" / 5" Angle Grinder
with non-locking paddle switch

NEW

Model	W9-125 600376420	WP9-125 Quick 600384420
Maximum wheel diameter	4-1/2" - 5"	4-1/2" - 5"
Amps	8.5	8.5
Rated input watts	900	900
No-load speed (RPM)	10,500	10,500
Maximum torque (inch lbs.)	22.1 inch lbs.	22.1 inch lbs
Switch Type	Lock-on slide	Non-locking paddle
LongLife motor	•	•
AC/DC capability	•	•
Auto-balance vibration control		
Metabo safety slip clutch	•	•
Quick wheel change system		•
Low profile aluminum die-cast gear housing	•	•
Rotatable gear housing	•	•
Burst-proof guard w/ 7 stops	•	•
Vibration dampened side handle		•
Auto-stop carbon brushes	•	•
Winding protection grid	•	•
Arbor size	7/8"	7/8"
Spindle thread	5/8"-11	5/8"-11
Tool weight	4.6 lbs.	4.6 lbs.
Shipping weight	6.03 lbs.	5.64 lbs.
Length	11.4"	11.4"
Carrying case (optional)	344454180	344454180
Standard equipment:		
Type 27 wheel guard	339204500	339204500
Side handle	316046590	316046590
Inner flange	341031290	341031290
Locking nut	341101480	316055450
Spanner wrench	623934000	
Optional equipment:		
Quick-Clip on Type 1 cutting guard	630352000	630352000



W12-125 Quick
4 1/2" / 5" Angle Grinder

NEW



WEP15-125 Quick
4 1/2" / 5" Angle Grinder
with non-locking paddle switch

NEW

Model	W12-125 Quick 600398420	WEP15-125 Quick 600476420
Maximum wheel diameter	4-1/2" - 5"	4-1/2" - 5"
Amps	10.5	13.5
Rated input watts	1250	1550
No-load speed (RPM)	11,000	11,000
Maximum torque (inch lbs.)	30.1 inch lbs.	31.0 inch lbs.
Switch Type	Lock-on slide	Non-locking paddle
LongLife motor	•	•
AC/DC Capability	•	
Metabo safety slip clutch	•	•
Quick wheel change system	•	•
Electronic features:		
Electronic speed stabilization (TC)		•
Current interruption protection		•
Soft start feature		•
Overload protection w/ LED		•
Low profile aluminum die-cast gear housing	•	•
Rotatable gear housing	•	•
Burst-proof guard w/ 7 stops	•	•
Anti-vibration side handle	•	•
Auto-stop carbon brushes	•	•
Winding protection grid	•	•
Arbor size	7/8"	7/8"
Spindle thread	5/8"-11	5/8"-11
Tool weight	5.5 lbs.	5.7 lbs.
Shipping weight	6.60 lbs.	6.54 lbs.
Length	12.4"	12.4"
Carrying case (optional)	344454180	344454180
Standard equipment:		
Type 27 wheel guard	339204500	339204500
Side handle	314000970	314000970
Inner flange	341031290	341031290
Locking nut	316055450	316055450
Optional equipment:		
Quick-Clip on Type 1 cutting guard	630352000	630352000
Dust filter	630791000	630792000



WEV10-125
Electronic Variable Speed
4 1/2"/ 5" Angle Grinder

NEW



WEV15-125 Quick
Electronic Variable Speed
4 1/2"/ 5" Angle Grinder

NEW



WEV15-125 HT
Electronic Variable Speed
4 1/2"/ 5" Angle Grinder

NEW

Model	WEV10-125 600388420	WEV15-125 Quick 600468420	WEV15-125 HT 600562420
Maximum wheel diameter	4-1/2" - 5"	4-1/2" - 5"	4-1/2" - 5"
Amps	9.5	13.5	13.5
Rated input watts	1000	1550	1550
No-load speed (RPM)	2800-10500	2800-11000	2800-9600
Maximum torque (inch lbs.)	23.9 inch lbs.	34.5 inch lbs.	37.2 inch lbs.
Switch Type	Lock-on slide	Lock-on slide	Lock-on slide
LongLife motor	•	•	•
Metabo safety slip clutch	•	•	•
Quick wheel change system		•	
Electronic features:			
Variable speed dial (VTC)	•	•	•
Current interruption protection	•	•	•
Soft start feature	•	•	•
Overload protection w/ LED	•	•	•
Low profile aluminum die-cast gear housing	•	•	•
Rotatable gear housing	•	•	•
Burst-proof guard w/ 7 stops	•	•	•
Vibration dampened side handle	•		
Anti-vibration side handle		•	•
Auto-stop carbon brushes	•	•	•
Winding protection grid	•	•	•
Arbor size	7/8"	7/8"	7/8"
Spindle thread	5/8"-11	5/8"-11	5/8"-11
Tool weight	4.6 lbs.	5.5 lbs.	5.5 lbs.
Shipping weight	6.60 lbs.	6.60 lbs.	6.53 lbs.
Length	11.4"	12.4"	12.5"
Carrying case (optional)	344454180	344454180	344454180
Standard equipment:			
Type 27 wheel guard	339204500	339204500	339204500
Side handle	316046590	314000970	314000970
Inner flange	341031290	341031290	341031290
Locking nut	341101480	316055450	341101480
Spanner wrench	623934000		623934000
Optional equipment:			
Quick-Clip on Type 1 cutting guard	630352000	630352000	630352000
Dust filter		630791000	630791000