



W12-150 Quick
6" Angle Grinder

NEW



WP12-150 Quick
6" Angle Grinder
with non-locking paddle switch

NEW

Model	W12-150 Quick 600407420	WP12-150 Quick 600418420
Maximum wheel diameter	6"	6"
Amps	10.5	10.5
Rated input watts	1250	1250
No-load speed (RPM)	9,600	9,600
Maximum torque (inch lbs.)	33.6 inch lbs.	33.6 inch lbs.
Switch Type	Lock-on slide	Non-locking paddle
LongLife motor	•	•
AC/DC capability	•	•
Metabo safety slip clutch	•	•
Quick wheel change system	•	•
Low profile aluminum die-cast gear housing	•	•
Rotatable gear housing	•	•
Burst-proof guard w/ 7 stops	•	•
Anti-vibration side handle	•	•
Auto-stop carbon brushes	•	•
Winding protection grid	•	•
Arbor size	7/8"	7/8"
Spindle thread	5/8"-11	5/8"-11
Tool weight	5.5 lbs.	5.5 lbs.
Shipping weight	6.54 lbs.	6.54 lbs.
Length	12.4"	12.4"
Carrying case (optional)	656304000	656304000
Standard equipment:		
Type 27 wheel guard	339204510	339204510
Quick-Clip on Type 1 cutting guard	630353000	630353000
Side handle	314000970	314000970
Inner flange	341031290	341031290
Locking nut	316055450	316055450
Optional equipment:		
Dust filter	630791000	630792000
Multiple position bar	627362000	627362000



WE15-150 Quick
Electronic 6" Angle Grinder

NEW



WEP15-150 Quick
Electronic 6" Angle Grinder
with non-locking paddle switch

NEW



WEP17-150 Quick
Electronic 6" Angle Grinder
with non-locking paddle switch

NEW

Model	WE15-150 Quick 600464420	WEP15-150 Quick 600488420	WEP17-150 Quick 600507420
Maximum wheel diameter	6"	6"	6"
Amps	13.5	13.5	14.5
Rated input watts	1550	1550	1700
No-load speed (RPM)	9,600	9,600	9,600
Maximum torque (inch lbs.)	34.5 inch lbs.	34.5 inch lbs.	38.1 inch lbs.
Switch type	Lock-on slide	Non-locking paddle	Non-locking paddle
LongLife motor	•	•	•
Metabo safety slip clutch	•	•	•
Quick wheel change system	•	•	•
Electronic features:			
Electronic speed stabilization (TC)	•	•	•
Current interruption protection	•	•	•
Soft start feature	•	•	•
Overload protection w/ LED	•	•	•
Low profile aluminum die-cast gear housing	•	•	•
Rotatable gear housing	•	•	•
Burst-proof guard w/ 7 stops	•	•	•
Anti-vibration side handle	•	•	•
Auto-stop carbon brushes	•	•	•
Winding protection grid	•	•	•
Arbor size	7/8"	7/8"	7/8"
Spindle thread	5/8"-11	5/8"-11	5/8"-11
Tool weight	5.7 lbs.	5.7 lbs.	5.7 lbs.
Shipping weight	6.54 lbs.	6.54 lbs.	7.29 lbs.
Length	12.4"	12.4"	12.4"
Carrying case (optional)	656304000	656304000	656304000
Standard equipment:			
Type 27 wheel guard	339204510	339204510	339204510
Quick-Clip on Type 1 cutting guard	630353000	630353000	630353000
Side handle	314000970	314000970	314000970
Inner flange	341031290	341031290	341031290
Locking nut	316055450	316055450	316055450
Optional equipment:			
Dust filter	630791000	630792000	630792000
Multiple position bar	627362000	627362000	627362000

4 1/2" - 6" Safety Brake Grinders



#1 IN SAFETY

Metabo angle grinders are known for their longevity, safety and innovative features that make them more comfortable, offering longer wheel life, longer tool life and ultimate safety!

METABO BRAKE TECHNOLOGY

- Stops grinding wheels in under 2 seconds
- Stops thin cutting wheels in under 1 second
- Greatly reduces the likelihood of injury from kickback or loss of control



The Auto-Balance Advantage = Reduced Vibration

- Less fatigue, more comfort
- Reduced possibility of cumulative work related disorders
- Up to 100% Longer Tool Life
- Up to 100% Longer Wheel Life (depending on model)



The Metabo Safety Package

- Auto-balancer System (depending on model)
- Metabo Brake Technology (depending on model)
- Ergonomic Anti-Vibration Side handle
- Metabo S-Automatic Safety Clutch
- Toolless, Burst-proof Guard
- Non-locking Paddle Switch designs



WPB12-125 Quick
4 1/2" / 5" Angle Grinder
with non-locking paddle switch and brake



NEW



WPB12-150 Quick
6" Angle Grinder
with non-locking paddle switch and brake



NEW

Model	WPB12-125 Quick 600428420	WPB12-150 Quick 600432420
Maximum wheel diameter	4-1/2" - 5"	6"
Amps	10.5	10.5
Rated input watts	1250	1250
No-load speed (RPM)	11,000	9,600
Maximum torque (inch lbs.)	30.1 inch lbs.	33.6 inch lbs.
Switch Type	Non-locking paddle	Non-locking paddle
LongLife motor	•	•
AC/DC capability	•	•
Mechanical brake technology	•	•
Metabo safety slip clutch	•	•
Quick wheel change system	•	•
Low profile aluminum die-cast gear housing	•	•
Rotatable gear housing	•	•
Burst-proof guard w/ 7 stops	•	•
Anti-vibration side handle	•	•
Auto-stop carbon brushes	•	•
Winding protection grid	•	•
Arbor size	7/8"	7/8"
Spindle thread	5/8"-11	5/8"-11
Tool weight	5.7 lbs.	6 lbs.
Shipping weight	6.54 lbs.	6.54 lbs.
Length	13.3"	13.3"
Carrying case (optional)	344454180	656304000
Standard equipment:		
Type 27 wheel guard	339204500	339204510
Quick-Clip on Type 1 cutting guard		630353000
Side handle	314000970	314000970
Locking nut	316055450	316055450
Optional equipment:		
Quick-Clip on Type 1 cutting guard	630352000	
Dust filter	630792000	630792000
Multiple position bar	627362000	627362000



WORLD'S FIRST
1700 WATT SMALL
ANGLE GRINDER!



WEPBA17-125 Quick
Electronic 5" Angle Grinder
with non-locking paddle switch,
brake and auto-balance

WEPBA17-150 Quick
Electronic 6" Angle Grinder
with non-locking paddle switch,
brake and auto-balance

NEW

NEW

Model	WEPBA17-125 Quick 600548420	WEPBA17-150 Quick 600552420
Maximum wheel diameter	4-1/2" - 5"	6"
Amps	14.5	14.5
Rated input watts	1700	1700
No-load speed (RPM)	11,000	9,600
Maximum torque (inch lbs.)	32.7 inch lbs.	38.1 inch lbs.
Switch Type	Non-locking paddle	Non-locking paddle
LongLife motor	•	•
Mechanical brake technology	•	•
Auto-balance vibration control	•	•
Metabo safety slip clutch	•	•
Quick wheel change system	•	•
Electronic features:		
Electronic speed stabilization (TC)	•	•
Current interruption protection	•	•
Soft start feature	•	•
Overload protection w/ LED	•	•
Low profile aluminum die-cast gear housing	•	•
Rotatable gear housing	•	•
Burst-proof guard w/ 7 stops	•	•
Anti-vibration side handle	•	•
Auto-stop carbon brushes	•	•
Winding protection grid	•	•
Arbor size	7/8"	7/8"
Spindle thread	5/8"-11	5/8"-11
Tool weight	6 lbs.	6.2 lbs.
Shipping weight	7.10 lbs.	7.23 lbs.
Length	13.4"	13.4"
Carrying case (optional)	344454180	656304000
Standard equipment:		
Type 27 wheel guard	339204500	339204510
Type 1 wheel guard		630353000
Side handle	314000970	314000970
Locking nut	316055450	316055450
Optional equipment:		
Quick-Clip on Type 1 cutting guard	630352000	
Dust filter	630792000	630792000
Multiple position bar	627362000	627362000