



W24-180 MVT  
7" Angle Grinder

**NEW**



W24-230 MVT  
9" Angle Grinder

**NEW**



W26-230 MVT  
9" Angle Grinder

**NEW**

Model # (lock-on trigger) # (non-locking deadman switch)	W24-180 MVT 606466420 US606466760	W24-230 MVT 606467420 US606467760	W26-230 MVT 606474420 US606474760
Maximum wheel diameter	7"	9"	9"
Amps	15	15	15
Rated input watts	2400	2400	2600
No-load speed (RPM)	8,500	6,600	6,600
Maximum torque (inch lbs.)	124 inch lbs.	150 inch lbs.	159 inch lbs.
LongLife motor	•	•	•
AC/DC capability	•	•	•
Safety lock to prevent accidental switching on of the tool	•	•	•
Low profile aluminum die-cast gear housing	•	•	•
Burst-proof guard w/ 7 stops	•	•	•
Anti-vibration (3 position) side handle	•	•	•
Twister 3-position rear handle for cutting/grinding	•	•	•
Auto-stop carbon brushes	•	•	•
Winding protection grid	•	•	•
Arbor size	7/8"	7/8"	7/8"
Spindle thread	5/8"-11	5/8"-11	5/8"-11
Tool weight	13.3 lbs.	13.6 lbs.	16.5 lbs.
Shipping weight	17 lbs.	17.3 lbs.	20.2 lbs.
Length	18"	18"	18"
Carrying case (optional)	623874000	623874000	623874000
<b>Standard equipment:</b>			
Type 27 wheel guard	339204020	339204010	339204010
Side handle	314000960	314000960	314000960
<b>Optional equipment:</b>			
Type 1 cutting guard	630357000	630356000	630356000

Optional Equipment:

For mounting Type 1 and Type 27 non-hubbed wheels



US655038000 Adaptor kit to mount Type 1 diamond blades on 7" - 9" grinders.



655039000 Adaptor kit to mount 7" - 9" Type 27 wheels w/o hub. 655052000 replacement nut.

Dustless 7" Convertible Shroud



655154000 Dustless 7" Convertible Shroud For concrete surface prep using 7" diamond cup wheels on W24-180, W24-230 or W26-230.

Professional Series Type 1 Cut-off Wheel Guard



630357000 Type 1 Cut-off wheel guard for 7" Grinders. 630356000 Type 1 Cut-off wheel guard For 9" Grinders.



W2000  
7" Angle Grinder



W2000  
9" Angle Grinder

Model # (lock-on trigger) # (non-locking deadman switch)	W2000 (7") 606418420 US606418760	W2000 (9") 606420420 US606420760
Maximum wheel diameter	7"	9"
Amps	15	15
Rated input watts	2000	2000
No-load speed (RPM)	8,500	6,600
Maximum torque (inch lbs.)	89 inch lbs.	115 inch lbs.
AC/DC capability	•	•
Safety lock to prevent accidental switching on of the tool	•	•
Low profile aluminum die-cast gear housing	•	•
Burst-proof guard	•	•
Ergonomic (3 position) side handle	•	•
Auto-stop carbon brushes	•	•
Arbor size	7/8"	7/8"
Spindle thread	5/8"-11	5/8"-11
Tool weight	12.5 lbs.	12.75 lbs.
Shipping weight	16.7 lbs.	17 lbs.
Length	19.5"	19.5"
Carrying case (optional)	623874000	623874000
<b>Standard equipment:</b>		
Type 27 wheel guard	316045010	316045000
Side handle	314000280	314000280
<b>Optional equipment:</b>		
Type 1 cutting guard	630386000	630387000

Optional Equipment:

For mounting Type 1 wheels



US655038000 Adaptor kit to mount Type 1 diamond blades on 7" - 9" grinders.

Dustless 7" Convertible Shroud



655154000 Dustless 7" Convertible Shroud For concrete surface prep using 7" diamond cup wheels on W24-180, W24-230, W26-230 or W2000.