

CK180 WATER-COOLED

CK180 & CK180V RIGID

HEAD STYLE	CABLE	CABLE LENGTH	STANDARD #	SUPERFLEX #
Rigid Head	TriFlex/ SuperFlex	12½ ft. (3.8m)	CK1812	CK1812SF
		25 ft. (7.6m)	CK1825	CK1825SF
Rigid Head w/ Valve	TriFlex/ SuperFlex	12½ ft. (3.8m)	CK1812V	CK1812VSF
		25 ft. (7.6m)	CK1825V	CK1825VSF

- Water-Cooled
- 180 amp ACHF or DCSP @ 100%
- 8-1/8" (20.6cm) 3-1/2 oz (99gm)
- 8 Series Head Accessories

CK180 & CK180V RIGID EXTRA LENGTH SERIES

HEAD STYLE	CABLE	CABLE LENGTH	STANDARD #	SUPERFLEX #
Long Head 4½ in. (114mm) Neck	TriFlex/ SuperFlex	12½ ft. (3.8m)	CKL1812	CKL1812SF
		25 ft. (7.6m)	CKL1825	CKL1825SF
Extra Long Head 7½ in. (190mm) Neck	TriFlex/ SuperFlex	12½ ft. (3.8m)	CKXL1812	CKXL1812SF
		25 ft. (7.6m)	CKXL1825	CKXL1825SF
Extra Extra Long Head 10½ in. (266mm) Neck	TriFlex/ SuperFlex	12½ ft. (3.8m)	CKXXL1812	CKXXL1812SF
		25 ft. (7.6m)	CKXXL1825	CKXXL1825SF

- Water-Cooled
- 180 amp ACHF or DCSP @ 100%
- 8 Series Head Accessories



CKL180
4-1/2" (11.4cm)

CKXL180
7-1/2" (19.0cm)

CKXXL180
10-1/2" (26.6cm)

CK180 REPLACEMENT PART PAGE LOCATOR:

8 Series Consumables: 57	Torch: 51	Handle: 51	Cables: 47	Adapter/Dinse: 39-42, 44
--------------------------	-----------	------------	------------	--------------------------

CK200 WATER-COOLED

CK200 & CK200V RIGID

HEAD STYLE	CABLE	CABLE LENGTH	STANDARD #	SUPERFLEX #
Rigid Head	TriFlex/ SuperFlex	12½ ft. (3.8m)	CK212	CK212SF
		25 ft. (7.6m)	CK225	CK225SF
Rigid Head w/ Valve	TriFlex/ SuperFlex	12½ ft. (3.8m)	CK212V	CK212VSF
		25 ft. (7.6m)	CK225V	CK225VSF

- Water-Cooled
- 250 amp ACHF or DCSP @ 100%
- 7-1/2" (19.0cm) 3 oz (85gm)
- 2 Series Head Accessories



CK200 & CK200V FLEX

HEAD STYLE	CABLE	CABLE LENGTH	STANDARD #	SUPERFLEX #
Flex Head	TriFlex/ SuperFlex	12½ ft. (3.8m)	CK212 FX	CK212SF FX
		25 ft. (7.6m)	CK225 FX	CK225SF FX
Flex Head w/ Valve	TriFlex/ SuperFlex	12½ ft. (3.8m)	CK212V FX	CK212VSF FX
		25 ft. (7.6m)	CK225V FX	CK225VSF FX

- Water-Cooled
- 250 amp ACHF or DCSP @ 100%
- 7-1/2" (19.0cm) 3 oz (85gm)
- 2 Series Head Accessories



CK200 REPLACEMENT PART PAGE LOCATOR:

2 Series Consumables: 54	Torch: 51	Handle: 51	Cables: 47	Adapter/Dinse: 39-42, 44
--------------------------	-----------	------------	------------	--------------------------

CK200 WATER-COOLED CONTINUED

CK200 RIGID EXTRA LENGTH SERIES

HEAD STYLE	CABLE	CABLE LENGTH	STANDARD #	SUPERFLEX #
Long Head 4½ in. (114mm) Neck	TriFlex/ SuperFlex	12½ ft. (3.8m)	CKL212	CKL212SF
		25 ft. (7.6m)	CKL225	CKL225SF
Extra Long Head 7½ in. (190mm) Neck	TriFlex/ SuperFlex	12½ ft. (3.8m)	CKXL212	CKXL212SF
		25 ft. (7.6m)	CKXL225	CKXL225SF
Extra Extra Long Head 10½ in. (266mm) Neck	TriFlex/ SuperFlex	12½ ft. (3.8m)	CKXXL212	CKXXL212SF
		25 ft. (7.6m)	CKXXL225	CKXXL225SF

- Water-Cooled
- 250 amp ACHF or DCSP @ 100%
- 2 Series Head Accessories



MAX-FLO

CKL200 4-1/2 inch (11.4cm)

CKXL200 7-1/2 inch (19.0cm)

CKXXL200 10-1/2 inch (26.6cm)

CK200 EXTRA LONG REPLACEMENT PART PAGE LOCATOR:

2 Series Consumables: 54 Handle: 51 Cables: 47 Adapter/Dinse: 39-42, 44

CKPF200 PENCIL FLEX WATER-COOLED

CKPF200 PENCIL FLEX

HEAD STYLE	CABLE	CABLE LENGTH	STANDARD #	SUPERFLEX #
Flex Head	TriFlex/ SuperFlex	12½ ft. (3.8m)	CKPF212	CKPF212SF
		25 ft. (7.6m)	CKPF225	CKPF225SF

- Water-Cooled
- 250 amp ACHF or DCSP @ 100%
- 6" (15.2cm) 3 oz (85gm)
- 2 Series Head Accessories



CKPF200 REPLACEMENT PART PAGE LOCATOR:

2 Series Consumables: 54 Torch: 51 Handle: 51 Cables: 47 Adapter/Dinse: 39-42, 44

CKT200 WATER-COOLED

CKT200 RIGID TURBINE TORCH

HEAD STYLE	CABLE	CABLE LENGTH	STANDARD #	SUPERFLEX #
Rigid Head [For 1/16" (1.6mm) Tungsten]	TriFlex/ SuperFlex	12½ ft. (3.8m)	CKT212-116	CKT212SF-116
		25 ft. (7.6m)	CKT225-116	CKT225SF-116
Rigid Head [For 3/32" (2.4mm) Tungsten]	TriFlex/ SuperFlex	12½ ft. (3.8m)	CKT212-332	CKT212SF-332
		25 ft. (7.6m)	CKT225-332	CKT225SF-332

- Water-Cooled
- 200 amp ACHF or DCSP @ 100%
- 14-1/2" (36.8cm) 4 oz (113.2gm)
- 9 Series Head Accessories
- 9" (254mm) torch body standard
- 5" (127mm) torch body available - contact factory



CKT200 REPLACEMENT PART PAGE LOCATOR:

9 Series Consumables: 57 Torch: 51 Handle: 51 Cables: 47 Adapter/Dinse: 39-42, 44

CKM200 WATER-COOLED

CKM200

HEAD STYLE	CABLE	CABLE LENGTH	STANDARD #	SUPERFLEX #
Rigid Head	TriFlex/ Superflex	12½ ft. (3.8m)	CKM212	CKM212SF
		25 ft. (7.6m)	CKM225	CKM225SF

- Water-Cooled
- 200 amp ACHF or DCSP @ 100%
- 6" (15.2cm) 3 oz (85gm)
- 2 Series Head Accessories



CKM200 REPLACEMENT PART PAGE LOCATOR:

2 Series Consumables: 54 Torch: 51 Handle: 51 Cables: 47 Adapter/Dinse: 39-42, 44



Follow us: [You Tube](#)



[Back To Table of Contents](#)

CK230 WATER-COOLED

CK230 & CK230V RIGID HEAVY DUTY SERIES

HEAD STYLE	CABLE	CABLE LENGTH	STANDARD #	SUPERFLEX #
Rigid Head	TriFlex/ SuperFlex	12½ ft. (3.8m)	CK2312	CK2312SF
		25 ft. (7.6m)	CK2325	CK2325SF
Rigid Head w/ Valve	TriFlex/ SuperFlex	12½ ft. (3.8m)	CK2312V	CK2312VSF
		25 ft. (7.6m)	CK2325V	CK2325VSF

- Water-Cooled
- 300 amp ACHF or DCSP @ 100%
- 8-1/4" (20.9cm) 3-3/4 oz (106gm)
- 2 Series Head Accessories



MAX-FLO.

CK230 & CK230V FLEX HEAVY DUTY SERIES

HEAD STYLE	CABLE	CABLE LENGTH	STANDARD #	SUPERFLEX #
Flex Head	TriFlex/ SuperFlex	12½ ft. (3.8m)	CK2312 FX	CK2312SF FX
		25 ft. (7.6m)	CK2325 FX	CK2325SF FX
Flex Head w/ Valve	TriFlex/ SuperFlex	12½ ft. (3.8m)	CK2312V FX	CK2312VSF FX
		25 ft. (7.6m)	CK2325V FX	CK2325VSF FX

- Water-Cooled
- 300 amp ACHF or DCSP @ 100%
- 8-1/4" (20.9cm) 3-3/4 oz (106gm)
- 2 Series Head Accessories



MAX-FLO.

CK230 REPLACEMENT PART PAGE LOCATOR:

2 Series Consumables: 54	Torch: 51	Handle: 51	Cables: 48	Adapter/Dinse: 39-42, 44
--------------------------	-----------	------------	------------	--------------------------

FL230 WATER-COOLED

FL230 FLEX-LOC SERIES

HEAD STYLE	CABLE	CABLE LENGTH	STANDARD #	SUPERFLEX #
FL2L	TriFlex/ SuperFlex	12½ ft. (3.8m)	FL2312	FL2312SF
		25 ft. (7.6m)	FL2325	FL2325SF

- Water-Cooled
- 230 Amps (w/FL2L) ACHF or DCSP @ 100%
- 7-3/4" (19.6cm) 5 oz (141gm)
- 2 Series Head Accessories



360°

FL230 REPLACEMENT PART PAGE LOCATOR:

2 Series Consumables: 54	Torch: 51	Handle: 51	Cables: 48	Adapter/Dinse: 39-42, 44
--------------------------	-----------	------------	------------	--------------------------

FL250 WATER-COOLED

FL250 FLEX-LOC SERIES

HEAD STYLE	CABLE	CABLE LENGTH	STANDARD #	SUPERFLEX #
FL3L	TriFlex/ SuperFlex	12½ ft. (3.8m)	FL2512	FL2512SF
		25 ft. (7.6m)	FL2525	FL2525SF

- Water-Cooled
- 250 Amps (w/FL3L) ACHF or DCSP @ 100%
- 7-3/4" (19.6cm) 5 oz (141gm)
- 3 Series Head Accessories



FL250 REPLACEMENT PART PAGE LOCATOR:

3 Series Consumables: 55	Torch: 51	Handle: 51	Cables: 48	Adapter/Dinse: 39-42, 44
--------------------------	-----------	------------	------------	--------------------------

CK300 WATER-COOLED

CK300 & CK300V RIGID

HEAD STYLE	CABLE	CABLE LENGTH	STANDARD #	SUPERFLEX #
Rigid Head	TriFlex/ SuperFlex	12½ ft. (3.8m)	CK312	CK312SF
		25 ft. (7.6m)	CK325	CK325SF
Rigid Head w/ Valve	TriFlex/ SuperFlex	12½ ft. (3.8m)	CK312V	CK312VSF
		25 ft. (7.6m)	CK325V	CK325VSF

- Water-Cooled
- 350 amp ACHF or DCSP @ 100%
- 9-1/2" (24.1cm) 6-1/2 oz (184gm)
- 3 Series Head Accessories



MAX-FLO.

CK300 REPLACEMENT PART PAGE LOCATOR:

3 Series Consumables: 55	Torch: 51	Handle: 51	Cables: 48	Adapter/Dinse: 39-42, 44
--------------------------	-----------	------------	------------	--------------------------

CK300 WATER-COOLED CONTINUED

CK300 & CK300V FLEX

HEAD STYLE	CABLE	CABLE LENGTH	STANDARD #	SUPERFLEX #
Flex Head	TriFlex/ SuperFlex	12½ ft. (3.8m)	CK312 FX	CK312SF FX
		25 ft. (7.6m)	CK325 FX	CK325SF FX
Flex Head w/ Valve	TriFlex/ SuperFlex	12½ ft. (3.8m)	CK312V FX	CK312VSF FX
		25 ft. (7.6m)	CK325V FX	CK325VSF FX

- Water-Cooled
- 350 amp ACHF or DCSP @ 100%
- 9-1/2" (24.1cm)
6-1/2 oz (184gm)
- 3 Series Head Accessories



MAX-FLO

CK300 REPLACEMENT PART PAGE LOCATOR:

3 Series Consumables: 55	Torch: 51	Handle: 51	Cables: 48	Adapter/Dinse: 39-42, 44
--------------------------	-----------	------------	------------	--------------------------

TL300 WATER-COOLED

TL300 & TL300V RIGID TRIM-LINE™ SERIES

HEAD STYLE	CABLE	CABLE LENGTH	STANDARD #	SUPERFLEX #
Rigid Head	TriFlex/ SuperFlex	12½ ft. (3.8m)	TL312	TL312SF
		25 ft. (7.6m)	TL325	TL325SF
Rigid Head w/ Valve	TriFlex/ SuperFlex	12½ ft. (3.8m)	TL312V	TL312VSF
		25 ft. (7.6m)	TL325V	TL325VSF

- Water-Cooled
- 350 amp ACHF or DCSP @ 100%
- 8" (20.3cm)
5 oz (141gm)
- 3 Series Head Accessories



TRIM-LINE™

MAX-FLO

TL300 & TL300V FLEX TRIM-LINE™ SERIES

HEAD STYLE	CABLE	CABLE LENGTH	STANDARD #	SUPERFLEX #
Flex Head	TriFlex/ SuperFlex	12½ ft. (3.8m)	TL312 FX	TL312SF FX
		25 ft. (7.6m)	TL325 FX	TL325SF FX
Flex Head w/ Valve	TriFlex/ SuperFlex	12½ ft. (3.8m)	TL312V FX	TL312VSF FX
		25 ft. (7.6m)	TL325V FX	TL325VSF FX

- Water-Cooled
- 350 amp ACHF or DCSP @ 100%
- 8" (20.3cm)
5 oz (141gm)
- 3 Series Head Accessories



TRIM-LINE™

TL300 REPLACEMENT PART PAGE LOCATOR:

3 Series Consumables: 55	Torch: 51	Handle: 51	Cables: 48	Adapter/Dinse: 39-42, 44
--------------------------	-----------	------------	------------	--------------------------

CK510 WATER-COOLED

CK510 RIGID

HEAD STYLE	CABLE	CABLE LENGTH	STANDARD #	SUPERFLEX #
Rigid Head	Separate Cables	12½ ft. (3.8m)	CK5112	CK5112SF
		25 ft. (7.6m)	CK5125	CK5125SF
Rigid Head w/ Valve	Separate Cables	12½ ft. (3.8m)	CK5112V	CK5112VSF
		25 ft. (7.6m)	CK5125V	CK5125VSF

- Water-Cooled
- 500 amp ACHF or DCSP @ 100%
- 9-1/4" (23.5cm)
6-3/4 oz (191gm)
- 3 Series or 51 Series Head Accessories



MAX-FLO

SMALLEST 500 AMP TORCH IN THE WORLD!

Uses .020" ~ 1/4" (0.5mm ~ 6.4mm) Tungsten

CK510 REPLACEMENT PART PAGE LOCATOR:

3 Series Consumables: 55	51 Series Consumables: 57	Torch: 51	Handle: 51	Cables: 48	Adapter/Dinse: 39-42, 44
--------------------------	---------------------------	-----------	------------	------------	--------------------------



Follow us: YouTube



Back To Table of Contents