

LN-23P Wire Feeder

Processes

Innershield (FCAW-S)

Product Number

K316L-1

See back for complete specs

Input Power

14-50V DC

Rated Output Current/Duty Cycle

350A/60%

Wire Size

.068 - 5/64 in. (1.7 - 2.0 mm)

Wire Feed Speed

30 - 170 IPM (0.76 - 4.3 m/min)

Weight/Dimensions (H x W x D)

27 lbs. (12.3 kg)

20.5 x 9 x 19 in.

(520 x 230 x 480 mm)

The LN-23P semiautomatic wire feeder is built for tough work sites and is an excellent choice for field erection and pipe welding applications. It's portable, easy to set-up, and ideal for welding in difficult environments.

FEATURES

- ▶ **Weighs less than 50 lbs. (22.7 kg)** including optional Magnum® Innershield® gun and 14 lb. (6.3 kg) coil of electrode.
- ▶ **Continuous wire feed speed control, voltage control and analog voltmeter are standard.**
- ▶ **Completely enclosed wire reel** keeps the wire free of contaminants.
- ▶ **Equipped with trigger interlock circuit to reduce operator fatigue.**
- ▶ **Gun-mounted two-position switch** allows on-the-fly change to 83% of the preset wire feed speed.
- ▶ **Electrode and control cable** quickly connect to power source.
- ▶ **One or two LN-23P wire feeders** can be directly connected to recommended Lincoln Electric power sources, but only one can be used at a time.

APPLICATIONS

- ▶ Construction
- ▶ Pipe



UNIT INCLUDES

- ▶ 25 ft. (7.6 m) Control Cable
- ▶ 25 ft. (7.6 m) 1/0 Electrode Cable
- ▶ 3/32 in. (2.4 mm) Drive Rolls and Guide Tubes

REQUIRED OPTIONS

- ▶ LN-23P Adapter Kit (K350 or K350-1)
- ▶ Magnum Self-Shielded Gun (K345-10)

INPUT



OUTPUT



Two Year Extended
Warranty Available in
the U.S.A. and Canada.



RECOMMENDED ACCESSORIES



GENERAL OPTIONS

LN-23P Adapter Kit

Allows the LN-23P to be connected to the power source, but only one can be used at a time. 115 AC input. Order K350 - for Terminal Strip connection.

Order K350-1 - for 14-pin MS-type connection



Magnum® Self-Shielded Gun

Rated 350 amps, 60% duty cycle, 90° nozzle. For .068 through 5/64 in. (1.7 through 2.0 mm) Innershield® wire. Includes reduced speed switch. 10 ft. (3.0 m).

Order K345-10

PRODUCT SPECIFICATIONS

Product Name	Product Number	Input Power	Rated Output Current/Duty Cycle	Wire Feed Speed Range ipm (m/min)	Wire Size Range in. (mm)	H x W x D inches (mm)	Net Weight lbs. (kg)
LN-23P	K316L-1	14-50V DC (90V DC Max. OCV)	350A/60%	30-170 (0.76-4.3)	.068-5/64 (1.7-2.0)	20.5 x 9 x 19 (520 x 230 x 480)	27 (12.3)

For best welding results with Lincoln Electric equipment, always use Lincoln Electric consumables.
Visit www.lincolnelectric.com for more details.

CUSTOMER ASSISTANCE POLICY

The business of The Lincoln Electric Company is manufacturing and selling high quality welding equipment, consumables, and cutting equipment. Our challenge is to meet the needs of our customers and to exceed their expectations. On occasion, purchasers may ask Lincoln Electric for information or advice about their use of our products. Our employees respond to inquiries to the best of their ability based on information provided to them by the customers and the knowledge they may have concerning the application. Our employees, however, are not in a position to verify the information provided or to evaluate the engineering requirements for the particular weldment. Accordingly, Lincoln Electric does not warrant or guarantee or assume any liability with respect to such information or advice. Moreover, the provision of such information or advice does not create, expand, or alter any warranty on our products. Any express or implied warranty that might arise from the information or advice, including any implied warranty of merchantability or any warranty of fitness for any customers' particular purpose is specifically disclaimed.

Lincoln Electric is a responsive manufacturer, but the selection and use of specific products sold by Lincoln Electric is solely within the control of, and remains the sole responsibility of the customer. Many variables beyond the control of Lincoln Electric affect the results obtained in applying these types of fabrication methods and service requirements.

Subject to Change – This information is accurate to the best of our knowledge at the time of printing. Please refer to www.lincolnelectric.com for any updated information.